

Datasheet EATON 3S450D

Aan de genoemde specificaties kunnen geen rechten worden ontleend, deze worden door de fabrikant verschaft.
Raadpleeg de fabrikant voor aanvullende toelichting.

Battery

Battery technology:	Sealed Lead Acid (VRLA)
Automatic battery test:	Y
Cold start:	Y

Design

Certification:	CE/EAC/Ukr/Cm/CB report
Safety:	IEC 62040-1; IEC 62040-2 C2; IEC 62040-3; IEC 62040-4; IEC 61643-11
Product colour:	Black,White
LED indicators:	Y

Features

UPS topology:	Standby (Offline)
Input frequency:	50/60 Hz
Input operation voltage (max):	284 V
Surge protection:	Y
Power protection features:	Overdischarge
Output operation voltage (min):	220 V
Output power:	270 W
Output power capacity:	450 VA
Output operation voltage (max):	240 V
Output frequency:	50 Hz
Maximum current:	10 A
Input operation voltage (min):	161 V

Operational conditions

Operating temperature (T-T):	0 - 40 °C
Operating altitude:	0 - 3000 m

Ports & interfaces

USB port:	N
AC outlets quantity:	6 AC outlet(s)

Weight & dimensions

Height:	86 mm
Weight:	2.9 kg
Width:	325 mm
Depth:	140 mm